

CUSHIONED SENSOR MOUNTS



Spring-loaded Sensor Protection Features

- * Spring-loaded housing mechanism
- * Plastic caps for shielded and unshielded sensors
- * Stainless Steel or anodized aluminum
- * Reduces downtime and replacement expenses
- * Reduces abrasion and impact damage
- * Speeds sensor installation and setup times
- * Reduces spare sensor inventories

Models	A	B	C	D	E	F	G	H	I	J	K	Notes
HSN-08	M8	M16	3.10	0.25	22.0	15.2	5.33	22.1	N/A		8.89 (0.35)	Model numbers with an "N" after the sensor thread size are for non-shielded sensors. Caps are plastic, housings are anodized aluminum. For stainless steel mounts, add "SS" to the end of the model number (except for LP models which are only available in stainless steel and do not require the "SS").
HSN-08N	x1	x1.5	(0.12)	(0.01)	(0.87)	(0.60)	(0.21)	(0.87)	9.51 (0.37)	11.0 (0.43)		
HSN-12-LP	M12	M18	4.06	0.51	24.0	22.9	6.35	21.1	N/A		12.1 (0.48)	
HSN-12N-LP	x1	x1	(0.16)	(0.02)	(0.95)	(0.90)	(0.25)	(0.83)	17.3 (0.68)	14.7 (0.58)		
HSN-18	M18	M30	5.10 (0.20)	0.76 (0.03)	35.8	29.7	8.38	29.7	N/A		12.4 (0.49)	
HSN-18N	x1	1.5			(1.41)	(1.17)	(0.33)	(1.17)	17.8 (0.70)	23.9 (0.94)		
HSN-30	M30	M47	5.10 (0.20)	0.76 (0.03)	51.0	43.7	7.62	37.3	N/A		14.5 (0.57)	
HSN-30N	x1.5	x1.5			(1.72)	(1.72)	(0.30)	(1.47)	22.9 (0.90)	38.6 (1.52)		

Dimensions

